



TORO® DINGO® TX 1000

COMPACT UTILITY LOADERS

Toro invented the category, now meet the **TORO DINGO TX 1000** that's redefining the compact utility loader. Designed with vertical lift loader arms, its 1,000-lb rated operating capacity delivers category crushing performance. The TX 1000 also offers outstanding hinge pin height of 81" (206 cm) to clear the side of 30-yard dumpsters and one-ton trucks for maximum jobsite productivity. Patented controls are easy to operate and an innovative foot-operated auxiliary control results in greater efficiency. The TX 1000 is a lightweight, maneuverable machine that packs unmatched strength and reach in a compact package for the ultimate working advantage.

FEATURES

VERTICAL LIFT LOADER ARMS

- The vertical lift loader arm design results in a rated operating capacity of 1,000 lbs.
- Increased load capacity and greater reach at full height deliver even stronger performance
- 81" (206 cm) hinge pin height allows attachments to easily clear the side of 30-yard dumpsters or one-ton trucks
- Vertical path of lift arms allows for more efficient vertical applications, such as augering or concrete breaking

HIGH DRIVE TRACK SYSTEM

- Kevlar® or steel reinforced tracks ensure maximum strength and durability
- Ideal for the demands of any jobsite to outperform on any surface, even sand or loose gravel
- Maximum maneuverability on uneven surfaces

EASY OPERATION

- Our patented traction control design is intuitive, easy to operate and effortless
- Auxiliary foot control maintains hydraulic flow to the attachment, freeing the operators hands to focus on ground speed and attachment positioning
- Dedicated operating platform with thigh and hip padding for increased operator comfort
- Suspended platform has clear line of sight to the attachment plate, machine, and jobsite for maximum visibility

POWERFUL AND EFFICIENT

- Kubota® D1305 diesel, Tier-4 compliant engine features high torque and increased displacement for the strongest Dingo yet
- Fast ground speeds up to 4.7 mph (7.6 km/h) in forward and reverse
- Dual fuel tanks offer all day productivity
- Easy engine access and belt-free design minimize maintenance



TX 1000 narrow track

DINGO TX 1000



TX 1000 wide track



MAXIMUM HEIGHT & REACH

81" hinge pin height allows operator to dump into 30-yard dumpster or side of one-ton truck.



TORO EXCLUSIVE CONTROLS

Effortless traction controls are easy to use for all-day productivity.



UNMATCHED STRENGTH

1,000-lb rated operating capacity to lift and transport heavy loads.

SPECIFICATIONS

	DINGO TX 1000 (MODEL 22327)	DINGO TX 1000 WIDE TRACK (MODEL 22328)	
ENGINE	Engine	Kubota® D1305 Diesel	
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Liquid Cooled	
	Fuel Tank	11.5 gallons (44 liters)	
	Oil Capacity	6.0 quarts (5.7 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	3,000 PSI	
	Hydraulic Flow	Traction: 13.3 gpm (each pump) Auxiliary: 15.2 gpm	
	Reservoir Capacity	15.2 gallons (57.5 liters)	
TRACKS	Standard	Sprocket-drive, 6 road wheels per side	
	Traction	Dual hydrostatic pump	
DIMENSIONS	Track Width	127.6" x 5.9" (324 cm x 15 cm)	127.6" x 9.5" (324 cm x 24 cm)
	Wheelbase	41" (10 cm)	
	Ground Clearance	6.0" (15 cm)	
	Overall Dimensions (WxLxH) With Bucket	34.2" x 100.7" x 53.2" (87 x 256 x 135 cm)	41" x 100.7" x 53.2" (104 x 256 x 135 cm)
	Overall Dimensions (WxLxH) Without Bucket	34.2" x 81.7" x 53.2" (87 x 208 x 135 cm)	41" x 81.7" x 53.2" (104 x 208 x 135 cm)
	Maximum Operating Height	105" (267 cm)	
	Hinge Pin Height	81" (206 cm)	
	Dump Height	61" (155 cm)	
	Dump Angle	40-degrees	
	Reach - Fully Raised	24.5" (62 cm)	
	Ground Speed	3.7 mph (6.1 km/h)	4.0 mph (7.6 km/h)
	Weight	2,785 lbs (1263 kg)	2790 lbs (1266 kg)
	Tip Capacity	2,857 lbs (1,296 kg)	3,071 lbs (1,393 kg)
	Rated Operating Capacity (35% of Tip Capacity)*	1,000 lbs (454 kg)	1,000 lbs (454 kg)
	Ground Pressure	5.6 PSI	3.6 PSI

*Per ISO 14397-1

